## Model 25 Injection Blow Molding



## **Standard Features**

- Programmable control system with touch screen
- Screw speed tachometer
- · Running time recorder
- Alarm system (visual and audible)
- Two pressure blow air
- · High and low plastifier temperature alarms
- · Cycle time indicator
- · Preform hot water manifold
- · Blow mold cooling manifold
- Choice of plastifier screws:
   General purpose for PE, PS and PP or special screws for PVC, PP and PET
- · Laser Electric preform detector
- · Current ANSI safety standards
- · Ceramic heater bands
- Integrated heat controls
- · Cycle counter
- Retains 30 sets of process parameters
- · Internal and external cooling

## **Options**

- Bottle Orientating Stripper System (B.O.S.S.)
- BOSS plus with vacuum
- Machine color finishes to customer specification
- Rotary Union for core rod temperature control
- · WYE Delta electric motor start
- Outboard cylinder reducing pressure (for smaller molds)
- · Automatic air system drain
- One year spare parts kit
- · Non split nozzle
- · Barrel fan cooling
- Air intensifiers





115 East Parkway Drive
Egg Harbor Township, NJ 08234 USA
Website: http://www.jomarcorp.com
Email: info@jomarcorp.com



<b>Machine Dimensions</b>	US	Metric
Length	81"	206 cm
Width	52"	132 cm
Height with 1.125" (28.57mm) 27:1 Screw	100"	254 cm
Installed Weight	10,400lbs	4,717kg

<b>General Specifications</b>	US	Metric	
Preform Clamp	21 US tons	19 metric tons	
Casting Area <sup>1</sup>	11.7 in² 7.5 in²	75.4 cm² 48.3 cm²	
Blow Mold Clamp	5 US tons	4.5 metric tons	
Shut Height	8.00"	203.2 mm	
Press Stroke	4.00"	101.6 mm	
Maximum Die Set (W x L)	12.50" x 10.75"	317 mm x 273 mm	
Max Trigger Bar Length*	8.33"	211.6 mm	
Max Swing Radius	13.44"	341.4 mm	
Shot Capacity 60 grams (HDPE) with	vith a 1.125" (28.57mm) diameter 27:1 L/D Vertical Screw		
Motor Size	Standard 20 hp (14.9kw)		
Recommended Power Service	100 amps @ 380V - 460V, 3 phase 50 - 60 hz		
Dry Cycle Time	2.0 seconds		
Average Power Consumption	11 kW		

- 1 For Standard resins LDPE, HDPE, PP etc use the larger area, For Engineering resins PC, PVC, PET, etc use the smaller casting area
- \* For information on available trigger bar lengths please contact Jomar